




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification n ^o 6: H02J 3/18, H02K 11/00, 3/30, 3/40		A1	(11) International Publication Number: WO 98/34315
			(43) International Publication Date: 6 August 1998 (06.08.98)
(21) International Application Number: PCT/SE98/00162		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 2 February 1998 (02.02.98)			
(30) Priority Data: 9700348-7 3 February 1997 (03.02.97) SE 9704421-8 28 November 1997 (28.11.97) SE			
(71) Applicant (for all designated States except US): ASEA BROWN BOVERI AB [SE/SE]; S-721 83 Västerås (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): LEIJON, Mats [SE/SE]; Hyvlargatan 5, S-723 35 Västerås (SE). GERTMAR, Lars [SE/SE]; Humlegatan 6, S-722 26 Västerås (SE). NYGREN, Jan-Anders [SE/SE]; Karlfeldtsgatan 27 B, S-722 22 Västerås (SE). TEMPLIN, Peter [SE/SE]; Björnajaktsvägen 20, S-722 42 Västerås (SE).			
(74) Agent: HOPFGARTEN, Nils; L. A. Groth & Co. KB, P.O. Box 6107, S-102 32 Stockholm (SE).		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: SERIES COMPENSATION OF ELECTRIC ALTERNATING CURRENT MACHINES



(57) Abstract

In a method of series compensating rotating electric alternating current machines (2) connected, directly or via a static current converter (28), to a three-phase distribution or transmission network (6), wherein the stator winding of the alternating current machine is Y-connected, a capacitive circuit (14) for the fundamental frequency of the voltage is connected in each phase between the down side of the winding and the earth point (20) of the distribution or transmission network (6). A device for such series compensation comprises a capacitive circuit (14) for the fundamental frequency of the voltage, connected between the down side of the winding and the earth point (20) of the distribution or transmission network (6).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SERIES COMPENSATION OF ELECTRIC ALTERNATING CURRENT
MACHINES

5 The present invention relates to a method and a device
for series compensating a rotating electric alternating
current machine connected, directly or via a static
current converter, to a three-phase distribution or
transmission network, wherein the stator winding of the
alternating current machine is Y-connected. The
10 invention also relates to a rotating electric machine
provided with such a series compensation device.

The invention refers primarily to electric alternating
current machines intended for use as generators in
15 power stations for generating electric power. A typical
operating range may be 36 to 800 kV, so that they can
be connected directly to all types of high-voltage
power networks. This is possible thanks to the use of
high-voltage insulated electric conductors with solid
20 insulation similar to cables for transmitting electric
power, in the following termed high-voltage cable. The
cable is also provided with an outer semiconducting
layer with the help of which its potential in relation
to the surroundings is defined.

25 A conductor is known through US 5,036,165, in which the
insulation is provided with an inner and an outer layer
of semiconducting pyrolyzed glassfiber. It is also
known to provide conductors in a dynamo-electric
30 machine with such an insulation, as described in
US 5 066 881 for instance, where a semiconducting
pyrolyzed glassfiber layer is in contact with the two
parallel rods forming the conductor, and the insulation

in the stator slots is surrounded by an outer layer of semiconducting pyrolyzed glassfiber. The pyrolyzed glassfiber material is described as suitable since it retains its resistivity even after the impregnation
5 treatment.

Series compensation on both high voltage transmission networks and distribution networks is already known.

10 Series compensation on both high voltage transmission networks and distribution networks is already known. It is also well known that geomagnetically induced currents can cause harmful heating in directly grounded power network system

15 From US, A1, 4,341,989 a device is also previously known for phase compensation of a multiphase rotating electric alternating current machine by connecting in series or in parallel with each phase winding a
20 capacitive element on the upside of the winding.

The object of the present invention is to provide a new method and a new device for lowering the system reactance through series compensation of the
25 alternating current machine in question as well as for preventing geomagnetically induced currents.

This object is achieved with a method and a device of the type described in the introduction, having the
30 features defined in claim 1 and claim 2, respectively.

According to the invention, thus, the compensation is performed on the down side of the windings, so that

low-voltage insulated capacitors can be used, which is not possible with series compensation in high-voltage transmission networks according to known technology. Less expensive capacitors can therefore be used in the device according to the invention, since they are protected by the machine itself and connected to the neutral point, which is at low potential in relation to earth. This solution is especially advantageous for the type of machines to which the present invention relates, since their upside is intended to be connected directly to high-voltage power networks.

According to an advantageous embodiment of the device according to invention, an over-voltage protection means is connected in parallel with the capacitors so that they are protected from any over-voltages that may appear in the event of a fault condition.

According to a second advantageous embodiment of the device according to the invention, a bandstop filter is arranged between the Y-point of the capacitor bank formed by the capacitors and the earth point of the distribution or transmission network, possibly with a low-ohmic resistor connected between the bandstop filter and the earth point. This resistor may be a neutral-point resistor, dimensioned for a harmless earth-fault current of a few tens of amperes. An earth fault in the alternating current machine or the generator is able to emit an earth-fault current via this resistor but, by controlling the earth-fault current, measures can be taken to disconnect the generator or possibly the faulty phase.

From a power network point of view any increase in transient machine reactance can also be efficiently compensated in this manner.

5 In the machine according to the invention the windings are preferably composed of cables having solid, extruded insulation, of a type now used for power distribution, such as XLPE-cables or cables with EPR-insulation. Such cables are flexible, which is an
10 important property in this context since the technology for the machine according to the invention is based primarily on winding systems in which the winding is formed from cable which is bent during assembly. The flexibility of a XLPE-cable normally corresponds to a
15 radius of curvature of approximately 20 cm for a cable 30 mm in diameter, and a radius of curvature of approximately 65 cm for a cable 80 mm in diameter. In the present application the term "flexible" is used to indicate that the winding is flexible down to a radius
20 of curvature of the order of four times the cable diameter, preferably eight to twelve times the cable diameter.

Windings in the present invention are constructed to
25 retain their properties even when they are bent and when they are subjected to thermal stress during operation. It is vital that the layers retain their adhesion to each other in this context. The material properties of the layers are decisive here,
30 particularly their elasticity and relative coefficients of thermal expansion. In a XLPE-cable, for instance, the insulating layer consists of cross-linked, low-density polyethylene, and the semiconducting layers

consist of polyethylene with soot and metal particles mixed in. Changes in volume as a result of temperature fluctuations are completely absorbed as changes in radius in the cable and, thanks to the comparatively slight difference between the coefficients of thermal expansion in the layers in relation to the elasticity of these materials, the radial expansion can take place without the adhesion between the layers being lost.

- 10 The material combinations stated above should be considered only as examples. Other combinations fulfilling the conditions specified and also the condition of being semiconducting, i.e. having resistivity within the range of 10^{-1} - 10^6 ohm-cm, e.g. 15 1-500 ohm-cm, or 10-200 ohm-cm, naturally also fall within the scope of the invention.

The insulating layer may consist, for example, of a solid thermoplastic material such as low-density polyethylene (LDPE), high-density polyethylene (HDPE), 20 polypropylene (PP), polybutylene (PB), polymethyl pentene (PMP), cross-linked materials such as cross-linked polyethylene (XLPE), or rubber such as ethylene propylene rubber (EPR) or silicon rubber.

- 25 The inner and outer semiconducting layers may be of the same basic material but with particles of conducting material such as soot or metal powder mixed in.

- 30 The mechanical properties of these materials, particularly their coefficients of thermal expansion, are affected relatively little by whether soot or metal powder is mixed in or not - at least in the proportions

required to achieve the conductivity necessary according to the invention. The insulating layer and the semiconducting layers thus have substantially the same coefficients of thermal expansion.

5

Ethylene-vinyl-acetate copolymers/nitrile rubber, butyl graft polyethylene, ethylene-butyl-acrylate-copolymers and ethylene-ethyl-acrylate copolymers may also constitute suitable polymers for the semiconducting layers.

10

Even when different types of material are used as base in the various layers, it is desirable for their coefficients of thermal expansion to be substantially the same. This is the case with combination of the materials listed above.

15

The materials listed above have relatively good elasticity, with an E-modulus of $E < 500$ MPa, preferably < 200 MPa. The elasticity is sufficient for any minor differences between the coefficients of thermal expansion for the materials in the layers to be absorbed in the radial direction of the elasticity so that no cracks or other damage appear and so that the layers are not released from each other. The material in the layers is elastic, and the adhesion between the layers is at least of the same magnitude as the weakest of the materials.

20

25

The conductivity of the two semiconducting layers is sufficient to substantially equalize the potential along each layer. The conductivity of the outer semiconducting layer is sufficiently large to contain

30

the electrical field in the cable, but sufficiently small not to give rise to significant losses due to currents induced in the longitudinal direction of the layer.

5

Thus, each of the two semiconducting layers essentially constitutes one equipotential surface, and these layers will substantially enclose the electrical field between them.

10

There is, of course, nothing to prevent one or more additional semiconducting layers being arranged in the insulating layer.

15 To explain the invention more clearly an embodiment of the device according to the invention will be described in more detail by way of example, with reference to the accompanying drawings in which Figure 1 shows an embodiment of the device according to the invention and
20 Figure 2 shows a cross section through the high-voltage cable used in the rotating electric machine according to the invention.

Figure 1 shows an alternating current machine 2 in the
25 form of a generator, the phase voltages of which are connected directly to the network 6 via isolators and breakers 4. Over-voltage protection means 8 and current measuring devices 10 are also provided on the output side of the generator 2.

30

The stator winding of the generator 2 is Y-connected and a series-compensation capacitor 14 is connected in each of the phases on the down side of the winding. A

bandstop filter 16 is connected to the Y-point of the capacitor bank and a neutral-point resistor 18 is connected to the earth point 20 of the network 6. Current measuring devices 22, 24 are also provided on this side of the generator 2.

Connecting a series capacitor 14 in each of the phases achieves series compensation of the alternating current machine 2, thereby lowering the system reactance.

Over-voltage protection means 26 and a resistance R are suitably provided in order to protect the capacitors 14 in the event of a fault condition.

The filter 16 has nothing directly to do with the invention and will not be described in more detail.

The neutral-point resistor 18 is dimensioned to limit earth faults to a harmless magnitude of a few tens of amperes. An earth fault in the generator 2 may thus result in an earth-fault current through the resistor 18, and controlling the magnitude of this current enables measures to be taken for disconnecting the generator and possibly the faulty phase.

Alternatively the generator 2 may be connected to the network via a converter 28, as indicated in Figure 1.

The field excitation of the generator has been omitted in Figure 1.

Figure 2 shows a cross section through a high-voltage cable 29 used in the rotating electric machine

according to the invention. The high-voltage cable 29 is composed of a number of strand parts 31 made of copper, for instance, and having circular cross section. These strand parts 31 are arranged in the middle of the high-voltage cable 29. Around the strand parts 31 is a first semiconducting layer 32. Around the first semiconducting layer 32 is an insulating layer 33, e.g. XLPE-insulation, and around the insulating layer 33 is a second semiconducting layer 34.

CLAIMS

1. A method of series compensating rotating electric alternating current machines (2) connected,
5 directly or via a static current converter (28), to a three-phase distribution or transmission network (6), wherein the stator winding of the alternating current machine is Y-connected, **characterized** in that a capacitive circuit (14) for the fundamental frequency
10 of the voltage is connected in each phase between the down side of the winding and the earth point (20) of the distribution or transmission network (6).

2. A device for series compensating rotating electric alternating current machines (2) connected,
15 directly or via a static current converter (28), to a three-phase distribution or transmission network (6), wherein the stator winding of the alternating current machine is Y-connected, **characterized** in that a capacitive circuit (14) for the fundamental frequency
20 of the voltage is connected in each phase between the down side of the winding and the earth point (20) of the distribution or transmission network (6).

25 3. A device as claimed in claim 2, **characterized** in that each capacitive circuit includes a capacitor (14).

4. A device as claimed in claim 3, **characterized**
30 in that an over-voltage protection means (26) is connected in parallel with the capacitors (14).

5. A device as claimed in any of claims 2-4, **characterized** in that a bandstop filter (16) is arranged between the Y-point of the capacitor bank formed by the capacitors (14), and the earth point (20) of the distribution or transmission network (6).

6. A device as claimed in claim 5, **characterized** in that a low-ohmic resistor (18) is connected between the bandstop filter (16) and the earth point (20) of the distribution or transmission network (6).

7. A rotating electric machine having windings drawn in slots in the stator, **characterized** in that the windings are wound using high-voltage cable and in that the machine is provided with a device as claimed in any of claims 2-6.

8. A machine as claimed in claim 7, **characterized** in that the high-voltage cable is of a type comprises a core having a plurality of strand parts, an inner semiconducting layer surrounding the core, an insulating layer surrounding the inner semiconducting layer, and an outer semiconducting layer surrounding the insulating layer.

9. A machine as claimed in claim 8, **characterized** in that the high-voltage cable has a diameter within the interval of 20-200 mm and a conducting area within the interval of 80-3000 mm².

10. A machine as claimed in any of claims 7-9, **characterized** in that the cable is flexible and the layers abut one another.

11. A machine as claimed in any of claims 7-10,
characterized in that said layers are of materials
having such elasticity and such coefficients of thermal
5 expansion that the changes in volume in the layers
caused by temperature fluctuations during operation are
absorbed by the elasticity of the materials, the layers
thus retaining their adhesion to each other upon the
temperature fluctuations that occur during operation.

10

12. A machine as claimed in any of claims 7-11,
characterized in that the materials in said layers have
high elasticity, preferably with a modulus of elasti-
city less than 500 MPa, preferably less than 200 MPa.

15

13. A machine as claimed in any of claims 7-12,
characterized in that the coefficients of thermal
expansion for the materials in said layers are
substantially the same.

20

14. A machine as claimed in any of claims 7-13,
characterized in that the adhesion between layers is of
at least the same magnitude as the strength of the
weakest of the materials.

25

15. A machine as claimed in any of claims 7-14,
characterized in that each of the semiconducting layers
essentially constitutes one equipotential surface.





Fig. 1

THIS PAGE BLANK (USPTO)

Fig. 2



THIS PAGE BLANK (USPTO)

1
INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 98/00162

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H02J 3/18, H02K 11/00, H02K 3/30, H02K 3/40
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H02J, H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4341989 A (T.SANDBERG ET AL), 27 July 1982 (27.07.82), column 1, line 1 - line 2; column 2, line 9 - line 12, figure 3	1-3
Y	--	4-15
Y	US 5510942 A (L.E. BOCK ET AL), 23 April 1996 (23.04.96), figure 1, abstract	4
Y	EP 0684679 A1 (ABB STROMBERG KOJEET OY), 29 November 1995 (29.11.95), figure 1, abstract	5,6
	--	

☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

13 July 1998

Date of mailing of the international search report

1998 -07- 14

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Hans Bagge af Berga
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/00162

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5036165 A (R.K.ELTON ET AL), 30 July 1991 (30.07.91), column 1, line 16 - line 60; column 2, line 26 - line 57, figure 1, abstract --	7-15
Y	ABB ELKRAFTHANDBOK, ABB Distribution AB, ISBN 91-970956-2-1, JORDNINGSSYSTEM, see pages 274-276 --	6
Y	US 4510077 A (R.ELTON), 9 April 1985 (09.04.85), column 1, line 41 - line 46; column 1, line 54 - line 57; column 1, line 62 - line 65, col 2, li 19-20,col. 3,li.37-41 col.4,li. 8-18, col.8,li. 21-41,li.67-68,col.5,li.1-3,li.34-40 --	10-12,14
A	DE 2400698 A (KRIM-SAMHALOV,IZMAIL), 10 July 1975 (10.07.75), see the whole document -- -----	1-15

INTERNATIONAL SEARCH REPORT
Information on patent family members

30/06/98

International application No.
PCT/SE 98/00162

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4341989 A	27/07/82	DK 99680 A EP 0015624 A FI 792947 A SE 416693 B,C SE 7902102 A	09/09/80 17/09/80 09/09/80 26/01/81 09/09/80
US 5510942 A	23/04/96	NONE	
EP 0684679 A1	29/11/95	FI 98009 B,C FI 942447 D FI 952555 A US 5663636 A	13/12/96 00/00/00 27/11/95 02/09/97
US 5036165 A	30/07/91	US 5066881 A US 5067046 A CA 1245270 A US 4853565 A	19/11/91 19/11/91 22/11/88 01/08/89
US 4510077 A	09/04/85	CH 664646 A,B DE 3439093 A,C FR 2554456 A,B GB 2148880 A,B JP 1789646 C JP 4078576 B JP 60131853 A	15/03/88 15/05/85 10/05/85 05/06/85 29/09/93 11/12/92 13/07/85
DE 2400698 A	10/07/75	NONE	

THIS PAGE BLANK (USPTO)